

- 4WD ARTICULATED LOADER
- LIFTING CAPACITY 1 TON
- ROPS, FOPS SAFETY

- QUICK HITCH
- GP BUCKET+ PALLET FORKS
- VARIOUS ATTACHMENT OPTIONS

JOYSTICK CONTROL

SPECIFICATIONS

Overall weight (kg) 1100

L×W×H 2195mm×980mm×2080mm

Rated load (kg) 500

Dump height (mm) 2750

Tyres 23/8.5-12

SPECIFICATION STANDARD ENGINE

- Kubota D1105
- 3 cylinder
- Water cooled
- Rated power 25hp(18.2KW)
- Rated speed(r/min)3000

TRANSMISSION

- Multitronic
- Top speed 10km/h



FINANCE OPTIONS AVAILABLE

* Subject to availability and conformation by quote

REPUTABLE BRAND LOADERS

EXTENSIVE MANUFACTURING EXPERIENCE

GLOBAL DISTRIBUTION

FACTORY DIRECT PRICING

MEETS AUSTRALIAN STANDARDS

ROAD REGISTERABLE

ENGLISH OPERATIONAL MANUAL

AIR CONDITIONING OPTIONAL

WARRANTY & STRONG 7 DAYS PER WEEK AFTER

SALES SERVICE

SPARE PARTS READILY AVAILABLE

AUSTRALIAN WIDE & INTERNATIONAL FREIGHT

AVAILABLE