

- 4WD ARTICULATED LOADER
- LIFTING CAPACITY 2.7 TON
- ROPS, FOPS SAFETY

- QUICK HITCH
- GP BUCKET+ HAY FORKS
- VARIOUS ATTACHMENT OPTIONS
- REVERSING CAMERA
- JOYSTICK CONTROL
- JOYSTICK CONTROL

SPECIFICATIONS

Overall weight (kg) 6400

L×W×H 6515mm×2074mm×2938mm

Rated load (kg) 2700

Dump height (mm) 3492

Tyres 16/70-24

SPECIFICATION STANDARD ENGINE

- YTO 4A4Z-24
- 4 cylinder diesel
- Water cooled
- Rated power 115hp (85Kw)
- Rated speed (r/min) 2400

TRANSMISSION

- Power shift 2 forward / 2 reverse gears
- Top speed 25 Km/h

FROM \$42,999*

FINANCE OPTIONS AVAILABLE

* Subject to availability and conformation by quote

REPUTABLE BRAND LOADERS

EXTENSIVE MANUFACTURING EXPERIENCE

GLOBAL DISTRIBUTION

FACTORY DIRECT PRICING

MEETS AUSTRALIAN STANDARDS

ROAD REGISTERABLE

ENGLISH OPERATIONAL MANUAL

AIR CONDITIONING OPTIONAL

WARRANTY & STRONG 7 DAYS PER WEEK AFTER

SALES SERVICE

SPARE PARTS READILY AVAILABLE

AUSTRALIAN WIDE & INTERNATIONAL FREIGHT

AVAILABLE

